

ABSTRACT

A channel quality report accuracy measurement apparatus and accuracy measurement method are provided
5 that correctly measure the accuracy of channel quality reported from a communication apparatus. A scheme control section (140) stores coding rates and modulation schemes corresponding to CQIs, and specifies the transmission scheme corresponding to a fixed CQI reported
10 from a CQI statistical processing section (230). A CQI decoding section (220) decodes a reported CQI contained in a received signal. The CQI statistical processing section (230) performs statistical processing of reported CQIs corresponding to test data transmitted prior to an
15 accuracy measurement test, and reports the most frequently reported CQI to the scheme control section (140) as a fixed CQI. A PER calculation section (260) calculates the PER in the communication apparatus from the reported CQI and Ack/Nack corresponding to test data
20 transmitted in accordance with the fixed CQI. A determination section (270) performs threshold value determination for the PER for each reported CQI value, and outputs the reported CQI scheme determination result.

[FIG.1]

REPORTED CQI

[FIG.2]

5 100: TRANSMITTING SECTION
TEST DATA OR ACCURACY MEASUREMENT DATA
110 CODING SECTION
120 MODULATION SECTION
130 RADIO TRANSMITTING SECTION
10 140 SCHEME CONTROL SECTION
200: RECEIVING SECTION
210 RADIO RECEIVING SECTION
220 CQI DECODING SECTION
230 CQI STATISTICAL PROCESSING SECTION
15 240 ACK DECODING SECTION
250 ACK PROCESSING SECTION
260 PER CALCULATION SECTION
270 DETERMINATION SECTION
DETERMINATION RESULT
20 300 ANTENNA DUPLEXING SECTION

[FIG.3]

400 RADIO RECEIVING SECTION
410 CHANNEL QUALITY MEASUREMENT SECTION
25 420 CQI GENERATION SECTION
430 MULTIPLEXING SECTION
440 MODULATION SECTION
450 RADIO TRANSMITTING SECTION

460 ANTENNA DUPLEXING SECTION

RECEIVE DATA

TRANSMIT DATA

5 [FIG.4]

START

ST1000 CQI STATISTICS ACQUISITION

ST1100 TRANSMISSION METHOD SELECTION

ST1200 PER CALCULATION FOR EACH CQI

10 ST1300 PER CORRESPONDING TO FIXED CQI \leq THRESHOLD VALUE
A?

ST1400 PER CORRESPONDING TO ONE LEVEL HIGHER CQI \leq
THRESHOLD VALUE B?

ST1500 PER CORRESPONDING TO ONE LEVEL LOWER CQI \geq THRESHOLD
15 VALUE C?

END

(19) 世界知的所有権機関
国際事務局



(43) 国際公開日
2004 年 8 月 5 日 (05.08.2004)

PCT


(10) 国際公開番号
WO 2004/066547 A1

- (51) 国際特許分類⁷: H04L 1/00 (71) 出願人 (米国を除く全ての指定国について): 松下電
器産業株式会社 (MATSUSHITA ELECTRIC INDUS-
(21) 国際出願番号: PCT/JP2003/015944 TRIAL CO., LTD.) [JP/JP]; 〒571-8501 大阪府 門真市
大字門真1006番地 Osaka (JP).
(22) 国際出願日: 2003 年 12 月 12 日 (12.12.2003)
(25) 国際出願の言語: 日本語 (72) 発明者; および
(75) 発明者/出願人 (米国についてのみ): 篠井 健一郎
(26) 国際公開の言語: 日本語 (SHINOI, Kenichiro) [JP/JP]; 〒233-0013 神奈川県 横
浜市 港南区丸山台2-37-37-302 Kanagawa (JP). 鈴木 秀
俊 (SUZUKI, Hidetoshi) [JP/JP]; 〒239-0847 神奈川県
(30) 優先権データ: 特願2003-16385 2003 年 1 月 24 日 (24.01.2003) JP 横須賀市 光の丘6-2-803 Kanagawa (JP).

[続葉有]

(54) Title: LINE QUALITY REPORT ACCURACY MEASUREMENT DEVICE AND ACCURACY MEASUREMENT METHOD

(54) 発明の名称: 回線品質報告の精度測定装置および精度測定方法



A...TEST DATA OR ACCURACY MEASUREMENT DATA
100...TRANSMISSION SECTION
110...ENCODING SECTION
120...MODULATION SECTION
130...RADIO TRANSMISSION SECTION
140...METHOD CONTROL SECTION
300...ANTENNA SHARING SECTION
200...RECEPTION SECTION
B...JUDGMENT RESULT
230...CQI STATISTIC PROCESSING SECTION
220...CQI DECODING SECTION
210...RADIO RECEPTION SECTION
270...JUDGMENT SECTION
260...PER CALCULATION SECTION
250...Ack PROCESSING SECTION
240...Ack DECODING SECTION

(57) Abstract: A line quality report accuracy measurement device and accuracy measurement method capable of accurately measuring the accuracy of line quality reported from a communication device. A method control section (140) contains an encoding ratio corresponding to the CQI and a modulation method and specifies a transmission method corresponding to the fixed CQI reported from a CQI statistic processing section (230). A CQI decoding section (220) decodes a report CQI contained in the reception signal. The CQI statistic processing section (230) statistically processes the report CQI corresponding to the test data transmitted prior to an accuracy measurement test and notifies the CQI which has been reported most frequently as a fixed CQI to the method control section (140). A PER calculation section (260) calculates PER in the communication device according to the report CQI and Ack/Nack corresponding to the test data transmitted in accordance with the fixed CQI. A judgment section (270) performs a threshold value judgment for PER for each report CQI value and outputs the judgment result of the accuracy of the report CQI.

(57) 要約: 通信装置から報告される回線品質の精度を正確に測定する回線品質報告の精度測定装置および精度測定方法。方式制御部 (140) は、CQI に対応する符号化率および変調方式を記憶しており、CQI 統計処理部 (230) から通知される固定 CQI に応じた送信方式を指定する。CQI 復号部 (220) は、受信信号に含まれる報告 CQI を復号する。CQI 統計処理部 (230) は、精度測定試験に先立って送信されたテストデータに対応する報告 CQI を統計処理し、最も頻繁に報告された CQI を固定 CQI として方式制御部 (140) へ通知する。P

[続葉有]



(74) 代理人: 鷺田 公一 (WASHIDA, Kimihito); 〒206-0034
東京都 多摩市 鶴牧1丁目24-1 新都市センタービル
5階 Tokyo (JP).

(81) 指定国 (国内): AE, AG, AL, AM, AT, AU, AZ, BA, BB,
BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE,
DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK,
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,
MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD,
SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG,
US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) 指定国 (広域): ARIPO 特許 (BW, GH, GM, KE, LS,
MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), ユーラシア特
許 (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), ヨーロッ
パ特許 (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,
TR), OAPI 特許 (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

添付公開書類:

— 国際調査報告書

2文字コード及び他の略語については、定期発行される
各PCTガゼットの巻頭に掲載されている「コードと略語
のガイダンスノート」を参照。